

B267

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 : <b>G11B 19/28</b>		A1	(11) International Publication Number: <b>WO 92/17883</b> (43) International Publication Date: <b>15 October 1992 (15.10.92)</b>
(21) International Application Number: <b>PCT/SE92/00095</b> (22) International Filing Date: <b>17 February 1992 (17.02.92)</b>		Published <i>With International search report. In English translation (filed in Swedish).</i>	
(30) Priority data: <b>9100904-3 26 March 1991 (26.03.91) SE</b>			
(71)(72) Applicant and Inventor: <b>OLSSON, Lennart [SE/SE]; Förvidargatan 13, S-216 21 Malmö (SE).</b>			
(81) Designated States: <b>AT (European patent), AU, BE (European patent), BG, CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, KR, LU (European patent), MC (European patent), NL (European patent), NO, SE (European patent), US.</b>			

(54) Title: **A METHOD AND A DEVICE FOR ALTERING OF THE ANGULAR VELOCITY OF A DRIVEN ROTATING MEDIA CARRIER**



**BEST AVAILABLE COPY**

(57) Abstract

A method and a device at a rotating media carrier in optical or magnetical recording and playback machines, whereby a radial displacement of at least one mass quickly and simply changes the angular velocity of the carrier, resulting in a considerably reduced access time to the information stored on the medium.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	RU	Russian Federation
CG	Congo	KP	Democratic People's Republic of Korea	SD	Sudan
CH	Switzerland	KR	Republic of Korea	SE	Sweden
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Thailand
DE	Germany	MC	Mauritania	TC	Togo
DK	Denmark			US	United States of America

A method and a device for altering of the angular velocity of a driven rotating media carrier.

This invention concerns a method to reduce the access time for rotating storage media with variable angular velocity by displacement of existing kinetic energy.

5 while at the same time the energy consumption is being reduced. The access time for rotating storage media is based on a radial displacement of the reading head and a pending of the correct position of the rotating disc (turning). In order to put a maximum of information on a circular, rotating disc surface, some storage media have been constructed according to the CLV (Constant Linear 10 Velocity) method, i. e. the disc is being read at a constant velocity along the track, thus constantly changing its angular velocity at recording or reading at different radial distances. Disc storage media with a partition in sectors could have the number of sectors as a step by step function of the radius.

The invention could for example be used on discs of the Compact Disc type.

15 which under continuous reading constantly change their angular velocity by keeping a constant reading speed along the information track. For applications of Compact Discs on computers, so-called CD-ROM, the angular velocity of the disc must in a short time and frequently be altered at each reading, as the information normally is scattered on different locations and thus at different radii 20 on the disc.

Certain sectorized storage media with an extended number of sectors with a extended number of radii also requires a change of the angular speed at recording or reading at different radii. Normally a relatively large quantity of energy and a powerful driver unit are required in order to alter the angular 25 velocity in a short time.

The cost for this is traditionally relatively high. Forces of actions and reactions often cause vibrations and thus interferences easily may arise when reading.

The purpose of the invention is to at a low cost considerably reduce the access time in machines of the above mentioned types. The purpose is achieved by the

method and the device in accordance with the applications for the patent.

The invention will be described below with reference to enclosed drawings, where fig. 1a and 1b show the concept and fig. 2 schematically shows how this is done in practice.

5 The rotating system (10) is provided with one or several masses (fig. 1a and 1b), attached so that they can be moved radially from the axis of rotation (17), shown at R1 and R2, altering the angular velocity without considerable supply of energy, without forces of reaction and in a very short time.

10 There is also a possibility to store the energy and have it transferred by other means to the rotating system, but in a way that does not affect the energy at a changed angular velocity. Thus this concerns a system with a constant energy and an altering rotating inertia.

Fig. 2 shows in detail how this is achieved in practice.

15 (10) represents a disc, connected to the end of a centrally placed spindle (11), which in its other end is a part of a driving gear (12). The spindle (13) protruding from driving gear (12) is connected to a system of at least one weight (16), which can be moved radially towards the axis of rotation (17) by means of an electromagnet or a stepping motor (18). The motor (14) supply the system with the energy necessary for rotation.

20 When a change of angular velocity for (10) and (11) is desired, energy can be transferred by a change of the radial position of at least one weight (16) by an electromagnet or a stepping motor (18).

25 The gear (12) changes the relations between the angular velocity for at least one weight (16) and the disc (10) and the spindle (11), so that energy requirements are less for the radial transfer of at least one weight (16), than had they been mounted directly on the spindle (11).

**Claims**

1. A method for altering the angular velocity ( $V_1, V_2$ ) of a driven, rotating media carrier (3) in optical or magnetical recording and reading machines, characterized by at least one mass M connected to the carrier (10), which is radially transferred in relation to the axis of rotation (17) of the carrier (10), so that the 5 rotation inertia of the media carrier (3) is varied with maintained energy.
2. Device for alteration of the angular velocity on a driven, rotating media carrier (10) in optical or magnetical recording and reading machines, characterized by: at least one weight mounted on the media carrier (10) or its driving shaft (11, 13). This weight is radially movable in relation to the axis of rotation (17) of the 10 media carrier, so that the rotation inertia of the media carrier is varied with maintained energy.
3. Device according to application no. 2, characterized by two weights (16) mounted diametrically opposite to each other, one on each side of the axis of rotation (17) of the media carrier (10).
- 15 4. Device according to application nos. 2 or 3, characterized by the weight or weights (16) being stored on the shaft (13) of the driving motor (14) on the media carrier (10) via a gear (12).

1/1

Fig. 1a




Fig. 1b





Fig. 2

**SUBSTITUTE SHEET**

# INTERNATIONAL SEARCH REPORT

International Application No. PCT/SE 92/00095

## I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all)<sup>6</sup>

According to International Patent Classification (IPC) or to both National Classification and IPC

IPC5: G 11 B 19/28

## II. FIELDS SEARCHED

Minimum Documentation Searched<sup>7</sup>

Classification System	Classification Symbols
IPC5	G 11 B

Documentation Searched other than Minimum Documentation  
to the Extent that such Documents are Included in Fields Searched<sup>8</sup>

SE, DK, FI, NO classes as above

## III. DOCUMENTS CONSIDERED TO BE RELEVANT<sup>9</sup>

Category <sup>10</sup>	Citation of Document <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>
A	CH, A, 245425 (OTTO JAEGER) 16 July 1947, see the whole document	1,2

### \* Special categories of cited documents:<sup>10</sup>

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the International filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the International filing date but later than the priority date claimed

"T" later document published after the International filing date of priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"Z" document member of the same patent family

## IV. CERTIFICATION

Date of the Actual Completion of the International Search

15th June 1992

Date of Mailing of this International Search Report

1992-07-01

International Searching Authority

Signature of Authorized Officer

SWEDISH PATENT OFFICE

BO GUSTAVSSON